

Camera AI Bullet



Mechanical

| | |
|---------------------|---|
| Dimensions | Without mount: Ø82 x 88.3 mm (Ø3.23 x 3.48") With wall mount: Ø82 x 153 mm (Ø3.23 x 6.02") |
| Weight | Without mount: 628 g (1.38 lb) With wall mount: 765 g (1.69 lb) |
| Enclosure materials | Aluminum alloy, polycarbonate |
| Mounting materials | Wall mount: aluminum alloy Pole mount: aluminum alloy |
| Weatherproofing | IP65 |
| Resistance | IK04 |

Optics

| | |
|------------|--|
| Sensor | 5 MP CMOS sensor |
| Lens | Fixed focal length |
| View angle | H: 84.7°, V: 46.2°, D: 99° |
| Night mode | IR LED illumination and an IR cut filter |

Video

| | |
|--------------------|--|
| Video compression | H.264, MJPG |
| Resolution | 4MP (2688 x 1512), 16:9 aspect ratio |
| Maximum frame rate | 30 FPS |
| Image settings | Brightness, contrast, sharpness, saturation, noise reduction, 50/60 Hz |

System

| | |
|-------------------------|---------------------------------------|
| Processor specs | Quad core Arm® Cortex®-A53 based chip |
| Memory information | 2 GB LPDDR4 |
| Management interface | UniFi Protect application |
| Networking interface | 10/100/1,000 MbE RJ45 |
| Flash memory support | 8GB eMMC |
| Max. power consumption | 7.68W |
| Power method | PoE |
| Supported voltage range | 37–57VDC |
| LED | R/G/B/W ring |
| Button | Factory reset |
| Mounting | Wall, pole mount (included) |
| Operating temperature | -20 to 40° C (-4 to 104° F) |
| Operating humidity | 10 to 90% noncondensing |
| Certifications | FCC, IC, CE |

Audio

| | |
|------------|-----------------------|
| Microphone | Yes (can be disabled) |
|------------|-----------------------|

Software

| | |
|----------------------|---------------|
| UniFi OS application | UniFi Protect |
|----------------------|---------------|

| | |
|------------|---------------------------------|
| Mobile app | UniFi Protect (iOS and Android) |
|------------|---------------------------------|

